

more interaction devices, such as a touch pad or screen, and/or control systems including feedback loops and control motors (e.g., feedback for sensing position and/or velocity; control motors for moving and/or adjusting components and/or quantities). A typical data processing system may be implemented utilizing any suitable commercially available components, such as those typically found in data computing/communication and/or network computing/communication systems.

[0041] The herein described subject matter sometimes illustrates different components contained within, or coupled with, different other components. It is to be understood that such depicted architectures are merely examples and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected”, or “operably coupled”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable”, to each other to achieve the desired functionality. Specific examples of operably couplable include but are not limited to physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components.

[0042] With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations may be expressly set forth herein for sake of clarity.

[0043] It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to;” the term “having” should be interpreted as “having at least;” the term “includes” should be interpreted as “includes but is not limited to;” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to inventions containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize

that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

[0044] While various aspects and embodiments have been disclosed herein, other aspects and embodiments will be apparent to those skilled in the art. The various aspects and embodiments disclosed herein are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

What is claimed is:

1. A method of exciting a dynamic tactile interface having a plurality of electrodes, the method comprising:
 - identifying an area within an image that is capable of tactile feedback;
 - identifying a first subset of the plurality of electrodes in the dynamic tactile interface corresponding to the area; and
 - applying a voltage to each of the electrodes of the first subset of the plurality of electrodes to create a desired state for each electrode corresponding to the area capable of tactile feedback.
2. The method of claim 1, further comprising:
 - determining a row and a column for each electrode of the first subset of the plurality of electrodes; and
 - applying excitation signals to a row encoder and a column encoder corresponding to the row and the column for each of the first subset of the plurality of electrodes.
3. The method of claim 2, further comprising:
 - exciting an individual electrode selected from the first subset of the plurality of electrodes if a decoder signal is received at a charge circuit associated with individual the electrode in response the excitation signals received at the row encoder and column encoder from the controller.
4. The method of claim 2, wherein the voltage applied to the individual electrode is based on the decoder signal received from the row encoder and the column encoder.
5. The method of claim 4, wherein applying a positive voltage to the individual electrode creates the desired state of an indentation.
6. The method of claim 4, wherein applying a negative voltage to the individual electrode creates the desired state of a protrusion.
7. The method of claim 3, further comprising:
 - detecting an input in the area within the image capable of tactile feedback;
 - identifying a new area within the image that is capable of tactile feedback;
 - identifying a second subset of the plurality of electrodes corresponding to the new area; and